

- ✓ **Height and width adjustable**
- ✓ **Quad bearing swivel**
- ✓ **For professional roof cleaners**



TECHNICAL DATA

Pressure 275 / 500 bar
Temperature 120°C
Inlet M22x1.5-M
 G1/4" F




DR-520

FEATURES


Height and width adjustable

The DR-520. Width is adjustable up to 90mm and 33mm in height. Will work for most roof designs adding safety and stability.



Safety Eye

Allows you to easily secure the roof cleaner with a safety rope or cable.



Pressure Gauge

Use the pressure gauge to monitor your cleaning pressure. This allows you to ensure proper pressure when cleaning a variety of roofing materials.



Ball Valve

Makes it easy and convenient to turn off the flow to the unit.



Rotor Arms

Can withstand up to 275 bar or 500 bar, are precision welded and balanced.



2cw2 (2 Arms / 2 Nozzles / 275 bar) Part No. 82.942 1/8" (ø 470mm)
2cw2 (2 Arms / 2 Nozzles / 500 bar) Part No. 82.941 1/4" (ø 470mm)
 Part No. 82.975 1/4" (ø 470mm)

Swiss Engineering

High rpm stainless steel swivel features 4x reinforced self lubricated stainless steel ball bearings for improved performance. The dual spring based carbide seal system, guarantees long lasting operation under tough conditions.



Pedal switch

For additional safety, Mosmatic recommends you turn your flow on and off using the optional pedal switch.



Part No. 80.987

DYU Swivel (500 bar)
 Part No. 59.916

DYT Swivel (350 bar)
 Part No. 59.907

| Name | Part No. | ø | Width | Height | Weight | Rotor Arm | HP- Nozzles |
|----------------|---------------|-----|---------|---------|--------|--------------|----------------|
| DR-520 | 80.651 | 520 | 550-640 | 195-228 | 14.5kg | 2x 1/8" NPTF | --- |
| DR-520* | 80.662 | 520 | 550-640 | 195-228 | 14.5kg | 2x 1/8" NPTF | --- |

* Pressure: 500 Bar / Inlet G1/4" F